



Catalog Home

Product Datasheet

**CHANCE**

**88135 -- Bust Anchor**



For more information or to place an order, please contact Supply Solutions at 866-978-7759.  
Courtesy of Hubbell Power Systems.

Expanding Anchor for 8" (203 mm) Hole used with 0.625" (15.9 mm) or 0.75" (19.1 mm) Diameter Rod

**Product Specifications**

|  |                                   |
|--|-----------------------------------|
| <b>Anchor Style</b>                    | Bust Anchor, Expanding Anchor     |
| <b>Component</b>                       | Expanding Anchor                  |
| <b>Rod Diameter - Order Separately</b> | 0.625" (15.9 mm), 0.75" (19.1 mm) |
| <b>Anchor Hole Size</b>                | 8" (152 mm)                       |
| <b>Coating</b>                         | Asphalt Coated                    |
| <b>Installation Tool</b>               | C302-0003                         |
| <b>Area</b>                            | 135 sq in (871 sq cm)             |
| <b>Industry Standards</b>              | RUS Accepted                      |
| <b>Material Type</b>                   | Standard                          |
| <b>UPC Code</b>                        | 09635907551                       |
| <b>Standard Package</b>                | 6                                 |
| <b>Standard Package Unit</b>           | EA                                |
| <b>Min Order Qty</b>                   | 6                                 |
| <b>Weight / Ea.</b>                    | 8.516 lbs                         |

**Notes**

Caution: All components of the Chance anchoring system are performance mated. Use of other anchoring products or equipment will not necessarily produce the same results.

**Compressed Product Number**

88135

**Holding Strength v. Soil Class**

| Catalog Number | Anchor Hole Size | Area Sq. In. | Rod Size (Order Separately) | 8-Way Anchor Holding Strengths (lbs) vs Chance Soil Class |         |         |         |         |
|----------------|------------------|--------------|-----------------------------|---|---------|---------|---------|---------|
|                |                  |              |                             | Class 3   | Class 4 | Class 5 | Class 6 | Class 7 |
| 6870           | 6"               | 70           | 5/8"                        | 16,000  | 14,000  | 11,000  | 8,500   | 5,000   |
| 88135          | 8"               | 135          | 5/8" or 3/4"                | 26,500+   | 22,000+ | 18,000+ | 15,000  | 10,000  |
| 1082           | 10"              | 200          | 1"                          | 31,000  | 26,500  | 21,000  | 16,500  | 12,000  |
| 1082-3/4       | 10"              | 200          | 3/4"                        | 31,000+   | 26,500+ | 21,000  | 16,500  | 12,000  |
| 1283           | 12"              | 300          | 1-1/4                       | 40,000  | 34,000  | 26,500  | 21,500  | 16,000  |
| 1283-1         | 12"              | 300          | 1                           | 40,000+   | 34,000  | 26,500  | 21,500  | 16,000  |

+ Ultimate strength of rod may limit holding strength

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

*All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.*

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.



For more informations or to place an order, please contact Supply solutions at 866-978-7759. Courtesy of Hubbell Power Systems.