



- HOME
- ABOUT KLEIN
- WHERE TO BUY
- WHAT'S NEW @ KLEIN
- ONLINE CATALOGS
- KLEIN BRAND MERCHANDISE
- KLEIN LITERATURE
- EVENTS
- SUPPLIER EXTRANET
- DISTRIBUTOR ACCOUNT SERVICE



## Tool Online Catalog

WHERE TO BUY

Select a Category

GO

### DEPTHFINDER™ STEEL FISH TAPES

[Product Index](#) > [Conduit Tools and Fish Tapes](#) > [Fish Tapes](#) > [Depthfinder™ Steel Fish Tapes](#) > 56004

#### Depthfinder™ High Strength 1/8" Wide Steel Fish Tape - 240'



Additional features:

*Permanent, laser etched 1' increments on the tape allow you to more accurately measure the depth of conduit runs and determine the amount of tape left to pay out.*

*The 13" case diameter means you can reel in 15% more tape in a single revolution than similar sized 12" tapes, saving you time and effort.*

[See Common Features](#)



Buy Now!



14:59:22 03-23-2010  
Chicago Weather



Pictured: 56003



Exclusive!  
Laser Etched  
Markings

Cat. No.	Description	Reel Diameter	Tape Size	Weight (lbs.)
56004	Depthfinder™ High Strength 1/8" Steel Fish Tape - 240'	13" (330 mm)	240' L x 1/8" W x .062" H (73 m L x 3 mm W x 1.5 mm H)	7.5

All dimensions are in inches and (millimeters) except where indicated.

[Download High-Resolution .jpg photo](#)

[Download High-Resolution .eps photo](#)



The downloadable files are compressed in .zip format to save on downloading times. Decompressing .zip files requires applications such as [WinZip](#) for the PC and [Stuffit Expander](#) for the Macintosh.

- ▲ WARNINGS:** Wear approved eye protection when feeding, pulling or rewinding fish tape.
- ▲ WARNINGS:** Do NOT use any fish tape on or near live circuits. Use extreme caution when working near any electrical equipment.
- ▲ WARNINGS:** Use a safe work position to avoid loss of balance when using fish tape.
- ▲ WARNINGS:** Never remove screws while fish tape is coiled inside reel.
- ▲ WARNINGS:** Never form pulling loop into a single loop (into shape of a fish hook) or create a sharp edge that could cause fish tape to catch on other objects or cut into insulation of surrounding wires. Pulling loop should only be formed into a double loop.

For questions regarding Klein Tools, please use the [Contact Klein Tools](#) page. For questions regarding Klein Tools' policy regarding the use of this site, please see our [Legal Notice/Privacy Statement](#).



For more information or to place an order,  
please contact Supply Solutions at  
866-978-7759.  
Courtesy of Klein Tools.