

# CHICAGO® GRIPS - FOR EXTRA-HIGH-STRENGTH CABLES

[Product Index](#) > [Wire Pulling Grips](#) > [Chicago® Grips](#) > [Chicago® Grips - for Extra-High-Strength Cables](#) > 1613-40

## Chicago® Grip for Extra-High-Strength Cables, Messenger, Guy Strand and Conductors

- A family of grips for cable sizes from .12" (3.10 mm) to 1.0" (25.4 mm).
- Double "V" grooves give four-point contact, reducing chance of slipping and providing proper alignment of wire and cable.
- For larger conductors, see our grips with round inside-jaw contour.



**Buy Now!**

Pictured: 1613-40

Cat. No.	Approx. Weight Each	Jaw Length	Maximum Cable	Maximum Safe Load - lbs	Maximum Safe Load - kg	Minimum Cable
1613-40	3 lbs. (1.36) g	4-3/16" (106)	.37" (9.4)	4500 lbs.	2045 kg	.12" (3.05)

All dimensions are in inches and (millimeters) except where indicated.

[Download High-Resolution .jpg photo](#)

[Download High-Resolution .eps photo](#)



The downloadable files are compressed in .zip format to save on downloading times. Decompressing .zip files requires applications such as [WinZip](#) for the PC and [Stuffit Expander](#) for the Macintosh.

**⚠ WARNINGS:** Before each use, clean jaw area and inspect grip for proper operation to avoid slippage.

**⚠ WARNINGS:** When used on/near energized lines, ground, insulate, or isolate grip before pulling.

**⚠ WARNINGS:** Do not exceed rated capacity.

**⚠ WARNINGS:** Always match proper size and type of grip to application.

**⚠ WARNINGS:** Grips are to be used for temporary installation, not for permanent anchorage.