

# WIRE PULLING GRIPS

## Klein Haven's® Grip

- Designed for use when light, compact grip is desired and where conductor damage is not a factor.
- Gripping pressure of the knurled jaw is applied to 1/4" (6.35 mm) cable area.



**Buy Now!**

Pictured: 1604-20

Line Art: 1604-20

Cat. No.	Approx. Weight Each	Maximum Cable	Maximum Safe Load - lbs	Maximum Safe Load - kg	Minimum Cable
1604-20	2.08 lbs. (1.14) g	steel strand .50" (12.7)	5000 lbs.	2272 kg	8 B&S solid .125" (3.18)

All dimensions are in inches and (millimeters) except where indicated.

[Download High-Resolution .jpg photo](#)

[Download High-Resolution .jpg lineart](#)

[Download High-Resolution .eps photo](#)

[Download High-Resolution .eps lineart](#)



The downloadable files are compressed in .zip format to save on downloading times.

Decompressing .zip files requires applications such as [WinZip](#) for the PC and [Stuffit Expander](#) for the Macintosh.

**▲ WARNINGS:** Before each use, clean jaw area and inspect grip for proper operation to avoid slippage.

**▲ WARNINGS:** When used on/near energized lines, ground, insulate, or isolate grip before pulling.

**▲ WARNINGS:** Do not exceed rated capacity.

**▲ WARNINGS:** Always match proper size and type of grip to application.

**▲ WARNINGS:** Grips are to be used for temporary installation, not for permanent anchorage.