

Grounding Clamps

Span Clamp




- Span clamp for steel messengered drop cable bonding applications. Unique locking design prevents rotation on steel strand.
- Mechanically galvanized ASTM B695.

Ordering Information

CATALOG NUMBER	DESCRIPTION	INNER PACK	OUTER PACK
SC03E-2G	For two steel messenger wires .051" to .072" diameter used on 1/4" (6.6m) steel strand	-	75

"I" Beam Grounding Clamp



- Grounding clamp used to bond a solid or stranded copper wire to steel structure.
- Mechanically galvanized ASTM B695.

Ordering Information

CATALOG NUMBER	DESCRIPTION	INNER PACK	OUTER PACK
SC07GG	Up to #10 AWG copper ground wire	-	125
SC07GG-185	Up to #6 AWG copper ground wire	-	100

"B" Ground Wire Clamp



- Used to secure #6 AWG to #12 AWG ground wire runs.
- Mechanically galvanized ASTM B695.
- 7/32" hole diameter.
- 3/8" wide x 9/16" long.



For more information or to place an order, please contact Supply Solutions at 866-978-7759.

PDF courtesy of Thomas & Betts.

Ordering Information

CATALOG NUMBER	DESCRIPTION	GROUND WIRE RANGE	INNER PACK	OUTER PACK
23-80002	"B" ground wire clamp	#12 (.081") to #6 AWG (.162")	500	5000

Ground Connector



- Ground connector used to connect various size copper ground conductors with a firm mechanical contact.
- Made of pure copper with brass fastener.



Ordering Information

CATALOG NUMBER	DESCRIPTION	INNER PACK	OUTER PACK
SC42-1	Connects #4 or #6 AWG to #10 AWG copper ground wire	150	1800