



- HOME
- ABOUT KLEIN
- WHERE TO BUY
- WHAT'S NEW @ KLEIN
- ONLINE CATALOGS
- KLEIN BRAND MERCHANDISE
- KLEIN LITERATURE
- EVENTS
- SUPPLIER EXTRANET
- DISTRIBUTOR ACCOUNT SERVICE



OPE Online Catalog

HOME

Select a Category

GO

CONNECTING DEVICES

[Product Index](#) > [Lanyards](#) > [Connecting Devices](#) > **87431**

Nylon-Webbing Lanyard – Fixed Length

Nylon-webbing lanyards are ideal for positioning and in situations where the worker is often turning or moving around (webbing will not reverse-twist [hockle]).

Equipped with two drop-forged steel, corrosion-resistant Klein-Lok® locking snap hooks with 11/16" (17 mm) throat opening.

1" (25 mm) wide orange nylon webbing impregnated with resin for greater durability and abrasion resistance.

For use in positioning, suspension, or retrieval systems. Can also be used with a deceleration unit for fall-arrest.

Lanyard is certified and compliant with CSA and ANSI requirements.



NOTE: Rope lanyards can be used with a deceleration unit for fall-arrest.

[Always follow the A-B-C rule when using.](#)

Pictured: 87431

Cat. No.	Length	Shipping Weight
87431	5' (1.5 m)	1.65 lbs.

All dimensions are in inches and (millimeters) except where indicated.

[Download High-Resolution .jpg photo](#)

[Download High-Resolution .eps photo](#)



The downloadable files are compressed in .zip format to save on downloading times. Decompressing .zip files requires applications such as [WinZip](#) for the PC and [Stuffit Expander](#) for the Macintosh.

[Warning Tags and Labels - Connecting Devices](#)

For questions regarding Klein Tools, please use the [Contact Klein Tools](#) page. For questions regarding Klein Tools' policy regarding the use of this site, please see our [Legal Notice/Privacy Statement](#).



For more information or to place an order, please contact Supply Solutions at 866-978-7759. Courtesy of Klein Tools.