

J2 Cable Lasher



HOME • ABOUT GMP • PRODUCTS • TUTORIALS • WHERE TO BUY • NEWS • CONTACT US



Click on image above for a larger view of the J2 Cable Lasher

The Model J2 Cable Lasher is used to lash a single aerial cable or numerous cables to a supporting strand or to an existing lashed cable with stainless steel lashing wire.

- Will lash any single or multiple aerial cables up to 3 in. (76 mm) diameter across on any suspension strand from 1/4 in. (6 mm) to 7/16 in. (11 mm). A factory modification will allow the lasher to accommodate 1/2 in. (12.7 mm) strand if necessary.

- Consists of a rotating drum supported on a carriage that provides the mounting for a driving mechanism, cable lifters, cable and strand rollers

- Each of two recessed magazines will hold a 1200 ft. coil of .045 in. (365 m of 1.1 mm wire) lashing wire (or 450 ft. of .065 in.). The Lashing Wire is fully recessed and covered by a gate.

- Features a fast setup procedure, quick coil loading, and automatic drum lock for easy span transfers and smooth forward travel

- J2 Lasers make overlashing easy. Just push down on the strand roller knob, rotate it a quarter turn and you can lash additional cables together on previously lashed cable

- Positive internal gear to gear mechanism has no chains or belts to stretch, slip or break

- Constructed with heat-treated, plated steel, stainless steel, brass and aluminum components. Contains sealed and oilless bearings to minimize maintenance and assure durability.

- Pre-drilled and tapped at the factory for mounting of the lasher



Lasher Guard
"Halo" (optional)

[Lasher Guard assembly instructions](#)

[Template kit Instructions for modifying older lashers to accept Lasher Guard "Halo"](#)

[J2 Operations and](#)



In response to customer's requests, GMP developed a J2 that's capable of large bundle overlashing. We've removed the strand lock and enlarged the opening to prevent cable from rubbing on the housing. Included is a removable front handle to aid in moving the lasher around a pole.

For more information or to place an order, please contact Supply Solutions at 866-978-7759. Courtesy of General Machine Products.

[Maintenance Manual](#)

[Parts Identification and pricing](#)

guard or "halo". For use when lashing in overgrown areas.

- The J2 and every GMP lasher is fully serviceable to "good-as-new" specifications at our factory and at factory-trained service locations around the globe.

- The lasher is furnished with a rugged lightweight storage chest with corrosion resistant hardware, recessed latches and a moisture-proof, tongue-in-groove design for maximum protection when not in use



- Supplied with a 6 ft. bridle rope assembly and snap hooks, and an information and operation manual

Ordering Information:

P/N	Description	Wire Dia.	Weight
86070	J2 Cable Lasher Standard	.045	46 lbs. (20.9 kgs)
86071	J2 Cable Lasher Modified for 450 ft. of .065 in. wire	065	46 lbs. (20.9 kgs)
86072	J2 Cable Lasher Modified for 1/2 " Strand	.045	46 lbs. (20.9 kgs)
86074	J2 Cable Lasher Without strand lock and relieved for overlashing	.045	46 lbs. (20.9 kgs)
03165	Bridle Rope Assembly only		3 lbs. (1.4 kg)
08189	Chest only		19 lbs. (8.6 kgs)
	J2 Cable Lasher w/Chest Shipping Weight		65 lbs. (29.6 kgs)
70190	Towing Lanyard 35 ft. (optional)		6 lbs. (2.7 kgs)
70012	Lasher Guard "Halo" (optional)		3 lbs. (1.4 kg)



[Home](#) • [About GMP](#) • [Products](#) • [Tutorials](#) • [Where To Buy](#) • [News](#) • [Contact Us](#)



For more information or to place an order, please contact Supply Solutions at 866-978-7759. Courtesy of General Machine Products.