




PRODUCT SEARCH



[HOME](#) [WHAT'S NEW](#) [SERVICE / SUPPORT](#) [WHERE TO BUY](#) [INSTRUCTION MANUALS](#) [COMPANY INFO](#)

PRODUCTS

Hand Tools
Holemaking
Bending
Fishing
Cable Pulling
Wire & Cable Termination
Voice Data Video
Testing & Measurement
Storage & Material Handling
Hydraulic Pumps &
Miscellaneous



Name:
Buried Line Locator

Cat #:
BLL-200

UPC #:
07796

Spec:
TRANSMITTER:
Operating Voltage 0-600 VAC, 0-300 VDC Current 13mA (open line),
150mA (live or shorted line)
Frequency 33.3kHz
Operating Temperature 0°F to 120°F (-17°C to 50°C) Size 7.5" x 4"
x 2.1" (190.5 mm x 101.6 mm x 53 mm)
Power 6 VDC (4 AA batteries)

RECEIVER:
Depth Range Measures: 0-15 ft. Traces: 0-20 ft. ±(10% reading +
0.2 ft.)
Depth Resolution 0.1 ft. increments
Passive Trace Frequency 12Hz-24kHz
Operating Temperature 0°F to 120°F (-17°C to 50°C) Size 4.1" x
8.5" x 38" (104.1 mm x 215.9 mm x 965.2 mm)
Power 6 VDC (4 AA batteries)

Total Unit Weight 12.36 lbs. (5.6 kg)

Description:

LED and LCD signal strength indicators make it quick and easy to find exact line location.

- Lightweight and ergonomically balanced.
- Automatic signal boost makes it easy to trace lines, even those with very weak signals.
- Receiver may be used in active or passive mode.
- Receiver locates multiple passive frequencies with a single setting.
- Receiver automatically locks out passive range when it detects a transmitter signal, reducing the chance of tracing other lines carrying weaker signals.
- Microprocessor based circuitry delivers increased accuracy and features auto-gain control in all environments
- Traces 20' (6m) underground and provides depth readings up to 15'
- Transmitter can be connected to live lines up to 600V
- Lifetime Limited Warranty
- Molded carrying case included



Instruction Manual(s):

© 2010 Greenlee Textron Inc., a subsidiary of [Textron Inc.](#) All rights reserved.

[Privacy Policy](#) [Terms of Use](#) [Careers](#) [Idea Submissions](#)



For more information or to place an order,
please contact Supply Solutions at
866-978-7759.
Courtesy of Greenlee Textron.