



For more information or to place an order, please contact Supply Solutions at 866-978-7759. Courtesy of Century Wire Products.

Stainless Steel Wire Rope Products

LASHING WIRE

Stainless Steel Lashing Wire is used in a lasher to lash a cable or combination of cables to a supporting strand. It is a specially controlled annealing process, which yields a uniform, fine grain structure throughout the wire length and cross section for best results. All lashing wire is manufactured in the USA in accordance with standard specifications for lashing wire and may be certified upon request. It is available in 430, 302, and 316 stainless steel alloy.

Lashing Wire Grade Types

Type 430 (S43000)

This is a magnetic thermally nonhardening ferritic stainless steel alloy containing 16-18% chromium with no nickel or molybdenum rendering it susceptible to corrosion attack.

Type 302 (S30200)

This is an austenitic nonmagnetic and thermally nonhardening stainless steel. Corrosion and oxidation resistance is provided by the 18-20% chromium and the 8% min. nickel content.

Type 316 (S31600)

This is also austenitic, nonmagnetic and thermally nonhardening stainless steel. In comparison to type 302, the nickel content is increased from 8% to 10% and includes the addition of up to 3% molybdenum.

Product Specifications:

Part No.	Type	Size	Temper	Tensile Strength	Average Break
.038SS302ACW	302	.038	Annealed	95,000-125,000 PSI	115 lbs.
.045SS302ACW	302	.045	Annealed	95,000-125,000 PSI	165 lbs.
.045SS430ACW	430	.045	Annealed	70,000-95,000 PSI	125 lbs.
.045SS316ACW	316	.045	Annealed	95,000-120,000 PSI	145 lbs.

Packaging:

Part No.	Ft/Coil	W.T. Coil	Wt/box of 6
.038SS302ACW	1,600	6.3	37 lbs.
.045SS302ACW	1,200	6.5	40 lbs.

.045SS430ACW	1,200	6.5	40 lbs.
.045SS316ACW	1,200	6.5	40 lbs.

Straight hub or tapered hub are available.

All weights and footage lengths are approximate. There are six (6) coils per box with total box weight described above. Footages length are plus/minus 30 ft. Pallet quantity is 378 coils or 63 boxes.

Contact Us



For more information or to place an order,
 please contact Supply Solutions at
 866-978-7759.
 Courtesy of Century Wire Products.

[home](#) | [about us](#) | [news](#) | [contact](#) | [español](#)